



章丘市金属颜料有限公司

ZHANGQIU METALLIC PIGMENT CO., LTD

Sangyuan Industrial Park, Zhangqiu City,
Shandong Province 250203, China.

Tel: 86-531-83261860 Fax: 86-531-83362598

PRODUCT DATA SHEET

ZP-7058

ALUMINUM PASTE

TECHNICAL DATA

• LEAFING

Grade	325 Mesh Grade
Screen Analysis	99.00% minimum through 325 mesh (wet method)
Non-Volatile Content	70.0% (± 2.0%) by weight
Average Particle Size.....	5±1 microns
Leafing value	80% (min)
Specific Gravity.....	1.58 g/cm ³
Solvent.....	Isoalkane

APPLICATIONS GUIDELINES

ZP-7085 is the premium leafing product produced by odorless solvents. The biggest feature of this series is extremely low odor and almost odorless. ZP-7085 imparts good whiteness and hiding power, which is suitable for inks and injection molding with high odor requirements industry.

RECOMMENDED DISPERSION PROCEDURE

Under slow agitation, add sufficient amount of solvent to the aluminum paste to develop a smooth pigment slurry. Then add further solvent of choice and vehicle system where needed.

All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.